

Applications:

- Security Lighting
- Wall-mounted luminaires and electrical boxes

Design Details

- Filtered silicon light sensor
- 190 Joule MOV surge protection
- Instant turn-on, standard 5-10 second turn-off time delay
- 1.5 footcandle turn-on level (ANSI Std.)
- 12", 200°C, 16 Ga. Stranded leads
- 1/2" straight pipe thread fits standard 1/2" knock-out or threaded connector
- Not approved for use on LED fixtures

Regulatory Listings

- ANSI C136.24 Compliant
- UL listed
- ROHS compliant

Operating Characteristics

- Voltage 105 to 305 VAC, 60Hz



ADDITIONAL FEATURES

Impact Resistant Polycarbonate Enclosure

Swivel Design: Allows the control to rotate 360° around its base and 180° around the built in knuckle for ease of mounting and aiming.

Six Year Warranty: The DSW series controls are warranted to be free of manufacturing quality defects for a period of (6) years from the date of sale.

ORDERING INFORMATION

Example: DSW124 12A U

Series Code & Voltage	Turn-on Level (ftc)	Sensor	Gray Color	Package Qty.
DSW124 120 – 277Volts	1 1.0 – 2.0 ftc Turn-on	2 Silicon Sensor, 5 – 10 second off-time delay	A	U 1 Unit J12 12 Units J50 50 Units

DIMENSIONS

